

□□ □□

□□ □□	SF0894
□□	□□6.0*20.03mm
□□	□□□:BeCu,Au on Ni □□ □□:□□, Au on Ni □□ □:SWP
□□□□□	6.0mm
□□ □□□□	4.8mm
□□□ □	1000±20%gf@load 4.8mm
MOQ	100PCS
□□	□/□
□□ □□	□□□□ □□ □ 5~15□

□□ □□

产品图

Materials (Plated) (材質與鍍層):  
 Barrel (針套) : Brass (黃銅) , Au on Ni Plated 2-3u"  
 Plunger (針軸) : BeCu (鍍銅) , Au on Ni Plated 2-3u"  
 Spring (彈簧) : SWP (琴鋼線) , /

Specifications (技術要求):  
 Full Stroke (滿沖程) : 6.0mm  
 Rated Stroke (額定沖程) : 4.8mm  
 Spring Force (額定彈力) : 1000g±20% @ Load 4.8mm

				GKS-373		胜峰探针		
						说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 0.5<X≤6 ±0.05 6<X≤10 ±0.10 10<X≤50 ±0.2 50<X≤100 ±0.3		
标记	类数	更改文件号	签字	日期	图样标记			质量比例
设计			标准化		S A			10:1
校对			审定					
审核			制图					
工艺			日期	2015.11.20	共 1 页	第 1 页		

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



## Measuring Equipment >



### Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



