□□ □□

□□	SFENG
□□ □□	SF-P020-B
□□	□□ □□ □□ □□ □□
□□ □□	7 □ □□□□□ □

□□ □□


SF-P020
-A2
-U
-E
-B
-F
-U3
-J
SF-R020-VR
SF-R020-VRW
SF-RL020-VR
SF-RL020-VRW
szshengfengdz.en.alibaba.com
Probe specifications SF-P020 PL020 (技术规格)
Recommended minimum Spacing(最小间距):
1.0mm(.0394 ")
Mounting hole size(钻孔尺寸): 0.75mm(.0295 ")
Full travel(行程): 2.0(.0787 ")
Spring force(弹簧压力): 80g(克)
Materials and finishes(材料及涂饰):
Plunger:SK4, Ni plated
Barrel:Phosphor bronze,Gold plated
Spring:Music wire,Gold plated
Current ration(额定电流): 1A(安培)
Contact resistance(接触电阻): 120mΩ(毫欧姆)
Receptacle specifications
Materials and finishes: Phosphor bronze,
Gold plated
SF-P020-B
SF-PL020-B L means Length

□□□ □□□

1. □□□ □□ □ □ □□□□ 24 □□ □□ □□□ □□.

2. □□□ □□ □□□□ □□□□, OEM□ □□□□□.

3. □□□ □□ □ □ □□□□ □□ □□□ □□□□ □□□ □□□□ □□□ □.

4. □□□ □□ □ □ □□□□ □□□ □□□□ □□ □□□ □□□ □□ □□.

□□ □□

PCB, ICT, FCT □□□ □□□□ □□□□□ □ (□□);

□□ □ (□□□) □□□ □□ □□ □□ □□□ □□□ □□□□□, □□ □□, □□□, □□□ & A; □□ □□ □□ □□□□;

BGA□ □□□ □□□□□□ □□ □□ □□□;

□□□ □□ □, □□ □, QZ □ VZ □□□ LM □;

□□ □□ □□□, □□□ □□□, □□ □□ □□;

□□□ & A; □□ / □□;

□□ □□ □□ □□, 30 # OK □□□, □□ □□ □□, POM, □ □□ □