

□□ □□

□□ □□	SF3763
□□	□□4.0*42.0mm
□□	□□□:□□, □□□□ □□:□□, □□□□ □: SUS
□□ □□	10.0mm
□□ □□□□	6.5mm
□□□ □	200±35gf@load 6.5mm
MOQ	100PCS
□□	□/□
□□ □□	5~15□ □□□□ □□ □

□□ □□

Materials(Plated) (材質與鍍層):
 Barrel(針套) : Brass(黃銅) , Ni Plated
 Plunger(針軸) : Brass(黃銅) , Ni Plated
 Spring(彈弓) : SUS (不銹鋼線) , /

Specifications (技術要求):
 Full Stroke(滿沖程) : 10.0mm
 Rated Stroke(額定沖程) : 6.50mm
 Spring Force(額定彈力) : 200±35gf@ load 6.50mm

					名称:		胜峰探针
					SF-GP3. 5X42-B (R0. 25)		
标记	处数	更改文件号	签字	日期	图样标记	视图	质量
设计			标准化		S	A	比例
校对			审定		⊕		1:1
审核			制图	HJQ	图纸编号:		
工艺			日期	2017-12-12	共	1	页
					第	1	页

说明:
 1. 所有尺寸单位为mm
 2. 未注图示尺寸公差:按GB1804-79 11级精度执行

□□ □□



1. raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products



6. Packing



Measuring Equipment >



Measuring Equipment:

1. Agilent current testing;
2. Quadratic element measurement
3. Load Curve Meter
4. Bond Test
5. Life Fatigue Test



