



RFQ 001

RFQ #	SFENG
RFQ 日期	75mil 0.001 0.001 0.001
RFQ #	SF-PA111
RFQ #	Cu, 0 / 0.001 0.001
RFQ #	0.001, 0.001
RFQ #	0.001000
RFQ #	1N (3.6 0.001)
MOQ	100 0.001

SF-P111



SF-P111-E



Probe specifications SF-P111(技术规格)

- Recommended minimum center(最小间距): 1.90mm(.0748 ")
- Mounting hole size(钻孔尺寸):
压克力: 1.35mm(.0532 ")
电木板、玻璃纤维板: 1.40mm(.0551 ")
- Full travel(行程): 6.3(.2481 ")
- Spring force(弹簧压力): 120g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)









1. 24 小時 24 小時 24 小時。
2. 24 小時 24 小時 24 小時 OEM 24 小時。
3. 24 小時 24 小時 24 小時 24 小時 24 小時 24 小時。
4. 24 小時 24 小時 24 小時 24 小時 24 小時 24 小時。

PCB, ICT, FCT □□□ □□□□ □□□ □□ □ (□□);

□□, □□ □□, □□□, □□□ □ □□□□□ □□□□□□ □□ □ □□ □□ □□ □□ □□□□ □□ □ (□□□);

BGA □ □□□ □□□□□□ □□ □□ □□□;

□□□□□ □□ □, □□ □, QZ □ VZ □□□□ LM □;

□□□ □□□, □□□ □□□, □□□□□ □□;

□□□ □ □□□□ / □□;

□□ □□ □□ □□, 30 # OK □□□, □□ □□ □□, POM, □ □□ □




1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection




5. Finished products



6. Packing



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope

□□□ & □□

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.



**FAST
DELIVERY**