

36-J / M3 36 36 36 SF-PA5.8

□□

| | |
|----------|---|
| □□ □□ | 36-J / M3 36 36 36 SF-PA5.8 |
| □□ □ □□□ | □□□ : □□, □□ □□ □□ □□ □□; □□ : □□ □□, □□□□ □□□□ □□□□ □; □ : □□□□□ □□; |
| □□□ □ | 400g |
| □□ □□ | 3-10 □ |
| □□ | DHL / TNT / UPS / □□□ |

EW/r-9EX8-SVd-JS

Materials (Plated) (材質與鍍層):

Barrel (針套) : Brass (黃銅) , Au on Ni Plated

Plunger (針軸) : Brass (黃銅) , Au on Ni Plated

Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):

Contact Resistance (接觸電阻) : 50mΩ

Full Stroke (滿沖程) : 10mm

Spring Force (額定彈力) : 400±10% load 10mm




| | | | | | | | |
|----|----|-------|-----|------------------|-------|--|--|
| | | | | 名稱 | | 胜峰探针 说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。 | |
| | | | | SF-PA5.8X36-J/M3 | | | |
| 标记 | 页数 | 更改文件号 | 签字 | 日期 | 图样标记 | 质量比例 | |
| 设计 | | | 标准化 | | S A | 4:1 | |
| 校对 | | | 审定 | | | | |
| 审核 | | | 制图 | 徐松孟 | | | |
| 工艺 | | | 日期 | 2016.10.07 | 共 1 页 | 第 1 页 | |



SFENG 有限公司

Shengyifurui 有限公司 Co., 专业生产各种规格、型号的五金零件及紧固件。产品符合 RoH 环保标准。

五金零件

| | | |
|--|--|---|
| Spring exhausted tester | DC power supply | Current resistance tester |
|  |  |  |
| Microscope | Tensile strength tester | Spring tester |
|  |  |  |

□□

