

□□ □□

□□□	SFENG
Item □□	SF-□□ □
□□	□□ □□
□□ □□	□□□ □□□ □□ 7 □□ □

□□ □□□

The image features the SFENG logo with the tagline "The China's The World's". To the right are three certification logos: RoHS (Restriction of Hazardous Substances), ISO 9001 (Quality Management System) by SGS, and CE (Conformity with European standards). Below these is a technical drawing of a yellow probe tip. The drawing shows a cylindrical probe with a rounded end and a central ring. Dimension lines indicate a total length of 15.4, with a 5.5 segment from the tip to the ring and a 9.9 segment from the ring to the end. Diameter specifications are given as $\phi 2.0$ for the tip, $\phi 4.0$ for the ring, and $\phi 2.5$ for the main shaft.

SFENG
The China's The World's

RoHS ISO 9001 SGS CE

15.4
5.5 9.9

$\phi 2.0$ $\phi 4.0$ $\phi 2.5$

WWW.SF-PROBE.COM

□□ □□

□ □ (□□) PCBs, ICT, FCT □□□ □;

□□, □□, □□□, □ □□ □□ □□ □□□ □□ □ (□□□) □□□ & □□; amp; □□ □□ □□□□;

BGA □ □□□ □□□; □□ □□ □□□







□ □□ □ □□ □□ □ □ LM QZ □ VZ □□□□;

□□ □□ □□□, □□□ □□ □□□□□□ □□□;

□□□ & □□; amp; □□□ / □□□;

□□ □□□ □□ □□, □□□ # 30 □□, □ □ □□, POM, □□ □ □.

□□ □□

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

□□ □□

