

00 00 00 00 00 00 0 SF-P125


00 00

Suzhou 0 0 00 co., 00 000 000, 00 0 00 000 00 0 00 & 00 00 000 0 0 00. 000 000 000 000 00, 000 00 000
00 00 000 00, 000 00 00 00 ISO9001-2008 0 0 00 000 0 000 000 rohs 000 00.


000 000 0 SF 000-P125 000

SF-P125


SF-R125-VCR




SF-R125-VSC



SF-R125-CR




SF-R125-SC



Probe specifications SF-P125(技术规格)

- Recommended minimum Spacing 最小间距): 3.17mm(.1248")
- Mounting hole size(钻孔尺寸):
压克力: 2.40mm(.0945")
电木板、玻璃纤维板: 2.45mm(.0965")
- Full travel(行程): 6.30(.2480")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Ni plated;
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current ration(额定电流): 5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)
- Connections(接线形式):
Crimp: R125-VCR, R125-CR
Solder cup: R125-VSC, R125-SC
Material of receptacle: brass, gold plated



SF-P125-E

