



□□	SFENG
□□ ITerm □□	SF-P100
□□	□□ □□
□□ □□	7 □ □□□□ □

### SF-P100

SF-P100-E

**Probe specifications SF-P100(技术规格)**

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger: Be Cu, Rh plated; SK4, Rh plated Barrel: Brass, Gold plated Spring: Stainless steel
- Current ration(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

### SF-R100

**Probe specifications SF-R100(技术规格)**

- Recommended minimum center(最小间距): 2.54mm(.1000")
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670") 电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环) Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)



SF-P100-D

**SFENG**  
The China's The World's



[www.chinapogopinsupplier.com](http://www.chinapogopinsupplier.com)

SF-P100-B

**SFENG**  
The China's The World's



[www.chinapogopinsupplier.com](http://www.chinapogopinsupplier.com)

## 關於我們

1. 我們提供 24 小時客戶服務。
2. 我們提供 OEM 服務。
3. 我們提供 24 小時客戶服務，並提供 24 小時客戶服務。
4. 我們提供 24 小時客戶服務，並提供 24 小時客戶服務。

## 我們提供

PCB, ICT, FCT 測試服務 (SMT);

□□ □ (□□□)□ □□ □□, □□□, □□□ & A□ □□ □ □□ □□ □□□ □□□ □□; A; A; □□ □□ □□□□;

BGA □□□ □□□□□□ □□ □□ □□□;



□ □□ □, QZ □ VZ □□□□ □ LM□□ □□ □;

□□ □□ □□□, □□□ □□□ □□ □□;

□□□ & A; A; A; □□□ / □□□;

□□ □□ □□ □□, □□□ # 30 OK, □□ □□ □□, POM, □ □□ □

□□ □□

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

