


00 00

00	SFENG
00 00	SF-P020-U
000	00 00 Becu, 0 00 00 00
0	00, 0 00 00 00
0	SK4 00 000
0 00	80g
00 00	2.0MM
00 00	1A
00 00	120mΩ
00	1.0mm 0
00 00 00	0.75
MOQ	(100) 0
00 00	7 00000 0 000

00 00

chinapogopinsupplier.com



### Probe specifications SF-P020 PL020 (寸)

- Recommended minimum center(最小间距): 1.0mm(.0394 ")
- Mounting hole size(钻孔尺寸): 0.75mm(.0295 ")
- Full travel(行程): 2.0(.0787 ")
- Spring force(弹簧压力): 80g(克)
- Materials and finishes(材料及涂饰):  
Plunger:SK4,Rh plated  
Barrel:Phosphor bronze,Gold plated  
Spring:Music wire,Gold plated
- Current ration(额定电流): 1A(安培)
- Contact resistance(接触电阻): 120mΩ(毫欧姆)

#### Receptacle specifications

Materials and finishes: Phosphor bronze,  
Gold plated

□□□ □□□

- 1.Reply 24 □□ □□ withn □□
- 2.Customized □□□□ □□□□, OEM □□
- 3.Delivery □□□ □□□□ □ □□ □□□ □□□ □
- 4.provide □□□ □□□□ □□ □□ □□ □□







□□ □□

- □□□ □ □ PCB, ICT, FCT □□□□□□ (□□)
- □□ □ (□□□) □□□ (usuallytemporary) □□□ □□□□□□
- , □□ □□□, □□□ & A □□□□□ □□ □□ □□;

interconnectApplications;

- 00 00 probef orBGA & A, semiconudtion 000;
- 00 0 000, coatingpin, LM 0 withQZ & A; VZseries;
- 00 00 000, 000 000, 00 00 ...
- 000 & A, 00 / 00;
- 00 00 00 compents, 30 # OKwire, 00 00 00, POM, Ironhinge 0

00 00

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

00 00

