

9tips PCB-testsonde

Productinformatie




productnaam	9tips PCB-testsonde
Grootte	50mil 75mil 100mil of op maat gemaakte pogo pin
Huidig rantsoen	0-50A
Lente kracht	aangepast
Contactweerstand	50m Ω

SF-P100




SF-P100-E



Probe specifications SF-P100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(1000°)
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670°) 电木板、玻璃纤维板: 1.75mm(.0689°)
- Full travel(行程): 6.40(.2520°)
- Spring force(弹簧压力): 200g
- Materials and finishes(材料及涂饰): Plunger: Be, Cu, Rh plated; SK4, Rh plated Barrel: Brass, Gold plated Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

SF-R100



Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距): 2.54mm(1000°)
- Mounting hole size(钻孔尺寸): 压克力: 1.70mm(.0670°) 电木板、玻璃纤维板: 1.75mm(.0689°)
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式): Crimp: R100-VCR2.5, R100-CR Solder cup: R100-VSC2.5, R100-SC Wire wrap: R100-VW2.5, R100-WW, R100-WW(双环2.5), R100-WW(双环)
- Terminal: R100-VW2.5(T), R100-WW双环2.5(T), R100-WW双环5.0(T), R100-WW双环(T)

Productie Stroom



1. Raw material warehouse



2. Lathe workshop



3. Assemble workshop



4. Quality inspection



5. Finished products




6. Packing

Test Uitrusting



1. Agilent current testing



2. Quadratic element



3. Load Curve Meter



4. Bond Test



5. Life Fatigue Test



6. Microscope

Verpakking en verzending

Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.

