Dubbel hoofd contact Pogo Pin Connector

Specificatie:

Merk	SFENG SONDE
Item Aantal	**Dubbele kop pogo pin** SF031U330U30
Plunjer	Becu
Vat	PhBz
De lente	SWP
plating	goud plated over- nikkel
De lente dwingen	30g of afgestemde
Contact Weerstand	<50m ohm
Stroom rantsoen	1A
MOQ	100st als wij hebben voorraad
Lood tijd	2-15 dagen na ontvangende de betaling

afbeelding Laten zien:



Onze voordelen:

1.we have 30 years experience in probe pin and have ourself factory.

2.we provide free sample and have a testing depa rtment.

3.we could manufacture products as your request.

4.we guarantee best price and good service.

Ons belangrijkste product:

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semic onductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ a nd VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig loc ks, POM, Iron hinge etc

Uitrusting testen:

Spring exhausted tester	DC power supply	Current resistance tester
Microscope	Tensile strength tester	Spring tester

Pakket:

胜蜂电子