




Product Specification

Brand	SFENG
Item number	SF-P020
Plating	Gold plated
Lead time	7 working days after receipt of payment


SF-P020




SF-R020-VR



SF-R020-VRW



SF-RL020-VR



SF-RL020-VRW

Probe specifications SF-P020 PL020 (技术规格)

- Recommended minimum center(最小间距): 1.0mm(.0394 ")
- Mounting hole size(钻孔尺寸): 0.75mm(.0295 ")
- Full travel(行程): 2.0(.0787 ")
- Spring force(弹簧压力): 80g(克)
- Materials and finishes(材料及涂饰):
Plunger:SK4,Rh plated
Barrel:Phosphor bronze,Gold plated
Spring:Music wire,Gold plated
- Current ration(额定电流): 1A(安培)
- Contact resistance(接触电阻): 120mΩ(毫欧姆)

Receptacle specifications

Materials and finishes: Phosphor bronze,
Gold plated

SF-P020-J



SF-P020-B



Our service

1. We can answer your request within 24 hours.
2. custom Design is available and OEM are welcome.
3. We can deliver the probe pins to our customers all over the world with speed and precision.
4. We can provide the lowest price with high quality products to our customers.

main products

spring pin (single) for PCBs, ICT, FCT testing etc;

Pogo pin (connector) to establish the connection between the two circuit boards for loading, location, battery, Semiconductor & amp; amp; interconnect applications;

double ended probe for BGA and semiconductor testing;

Universal pin without spring coat pin, pin LM with QZ and VZ series;

High current probe, Switch probe needle capacitance;

Terminal & amp; amp; receptacle / plug;

Other related electronic components, wire # 30 OK, Jig locks, POM, hinge iron etc.

Quality control

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

Packing Photo

