


Product Specification


Brand	SFENG
Item number	SF-P100
Plating	Gold plated
Lead time	7 working days after receipt of payment

SF-P100


SF-P100-E

Probe specifications SF-P100(技术规格)


- Recommended minimum center(最小间距):
2.54mm(.1000")
- Mounting hole size(钻孔尺寸):
压克力: 1.70mm(.0670")
电木板、玻璃(纤维板): 1.75mm(.0689")
- Full travel(行程): 6.40(.2520")
- Spring force(弹簧拉力): 200g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated; SK4, Rh plated
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)




Noted: Specifications subject to change without notice 注：规格变动不另行通知

SF-R100


SF-R100-SC




SF-R100-VCR2.5




SF-R100-CR




SF-R100-VW2 5(T)



SF-R100-WW双环2.5(T)




SF-R100-WW双环5.0 (T)




SF-R100-WW双环(T)




SF-R100-VSC2.5




SF-R100-WW



SF-R100-WW (双环2.5)



SF-R100-WW (双环)



SF-R100-VW2.5

Probe specifications SF-R100(技术规格)

- Recommended minimum center(最小间距):
2.54mm(1000")
- Mounting hole size(钻孔尺寸):
压力为: 1.70mm(.0670")
- 电木板、玻璃纤维板: 1.75mm(.0689")
- Materials and finishes(材料及涂饰):
Barrel: Brass, Gold plated
- Connections(接线形式):
Crimp: R100-VCR2.5, R100-CR
Solder cup: R100-VSC2.5, R100-SC
Wire wrap: R100-VW2.5, R100-WW,
R100-WW(双环2.5), R100-WW(双环)
Terminal: R100-VW2.5(T), R100-WW双环2.5(T),
R100-WW双环5.0(T), R100-WW双环(T)

Noted: Specifications subject to change without notice/注：规格变动不另行通知

-20-

Product Image

SF-P100-J

SFENG
The China's The World's



WWW.SF-PROBE.COM

SF-P100-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

Our service

1. We can answer your request within 24 hours.
2. custom Design is available and OEM are welcome.
3. We can deliver the probe pins to our customers all over the world with speed and precision.
4. We can provide the lowest price with high quality products to our customers.

main products

spring pin (single) for PCBs, ICT, FCT testing etc;

Pogo pin (connector) to establish the connection between the two circuit boards for loading, location, battery, Semiconductor & amp; amp; interconnect applications;

double ended probe for BGA and semiconductor testing;







Universal pin without spring coat pin, pin LM with QZ and VZ series;

High current probe, Switch probe needle capacitance;

Terminal & amp; amp; receptacle / plug;

Other related electronic components, wire # 30 OK, Jig locks, POM, hinge iron etc.

Quality control

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

Packing Photo

