

Product Picture



PV1-H-H M7-24.5

Technical drawing showing dimensions: $\phi 2.0$, $\phi 6.0$, $\phi 9.0$, M7.0 \times 0.75, S7.0, $\phi 1.5$, 2.0, 7.0, 1.5, 10.0, 4.0, 24.5, 44.5, 7.0, 9.0. Cross-section A-A shows a hexagonal base with a diameter of 7.0 mm and a height of 9.0 mm.

Materials(Plated) (材質與鍍層):
 ①Barrel(針套) : Brass(黃銅) , Au on Ni Plated
 ②Plunger(針軸) : Brass(黃銅) , Au on Ni Plated
 ③Plunger(針軸) : Beta(鍍銅) , Au on Ni Plated
 ④Spring(彈弓) : SUS304 (不鏽鋼線) , /

Specifications (技術要求):
 Current Rating(額定電流) : 30A
 Contact Resistance(接觸電阻) : <50m Ω

彈力規格	名稱	移動距離(mm)	全壓值 (g)	全壓縮 (g)
1	電流針② 電壓針③	8 2	550 -	800 250
2	電流針 電壓針	/ /	/ /	/ /

名稱					勝峰探針	
PV1-H-H M7-24.5					說明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 10级精度执行。	
标记	数量	更改文件号	签字	日期	图样标记	质量比例
设计					SA	3:1
校对						
审核						

Our Service

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.

3. We can deliver the probe pins to our clients all over the world with speed and precision.

4. We can provide the lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control



Packing Picture

