

## Product Specification

Brand	SFENG
Item number	SF-P125
Plunger	Brass or Becu,gold or Ni plated
Barrel	Brass,gold or Ni plated
Spring	SK4,music wire
Spring Force	200g
Full Travel	6.3mm
Current Ration	5A
Current Resistance	50mΩ
Pitch	2.45mm
Mounting hole size	1.7mm
MOQ	100 pcs
Lead time	7 working days after receiving the payment

## Product Picture



## Our Service







- 1.Reply your inquiry withn 24 working hours
- 2.Customized design is available,OEM are welcomed
- 3.Delivery the probe pins to our clients all over the world with speed and precision
- 4.provide the lowest price with high quality to our client

## Main Products

- Spring loaded pin(single) for PCB,ICT,FCT testing,etc;
- Pogo pin(connector) to establish a(usuallytemporary)connection between two printed circuit boards for charing, locating, Battery, Semiconductor & interconnectApplications;
- Double ended probef orBGA&semiconudtion testing;
- Universal pin without spring,coatingpin,LM pin withQZ&VZseries;
- High current probe,Switch probe,Capacitance needle...
- Terminal&receptacle/socket;

---Other related electronic compents,30#OKwire,Jig locks,POM,Ironhinge,etc

## Quality Control

Spring exhausted tester	DC power supply	Current resistance tester
 A large, white, industrial-grade machine with a glass door and a control panel on the right side.	 A white, rectangular device with a black top panel. The front panel features a red power switch, several knobs, and output terminals. The text "YoRi ADJUSTABLE DC POWER SUPPLY" is visible on the top.	 A white, rectangular device with a large green digital display showing "8.88.8". It has a control knob and a warning symbol on the right side.
Microscope	Tensile strength tester	Spring tester
 A white and black compound microscope with a stage and objective lenses.	 A blue and white machine used for testing the tensile strength of materials, featuring a vertical column and a sample holder.	 A white machine used for testing springs, with a vertical column and a control panel on the front.

## Packing Picture

