## *Specifications*

| | |
|---|---|
| Brand | SFENG |
| Model | SF-PV1-H-H3.0*33.2 |
| Plunger | Beryllium Copper |
| Body | Brass |
| Spring | SUS |
| Spring force | 200g |
| Working travel | 1.0mm |
| Plated | Gold plated |
| Current Resistance | 50mΩ |
| Spacing | / |
| Mounting dimensions | / |
| MOQ | 500 |
| delivery time | 15 Days after confirming order |

## *Customized probe pin Image*

*Customized probe pin drawing*




***our service***

1. Quick response.

2. Customized is accepted.

3. Short production time and fast delivery.

4. High quality and good price.

## *Main products*

Spring-loaded pin (single) of PCB, ICT, FCT testing;

Spring pin (connector) to establish a connection between two printed circuit boards for charging, positioning, batteries, semiconductors and amplifiers; interconnect applications;

BGA and semiconductor test double-ended probe;

Universal pin no spring, paint needle, LM pin QZ and VZ series;

High current probe, the probe switches, capacitors needle;

Pier and amplifier; socket / socket;

Other related electronic components, 30 # OK line, jig lock, POM, iron hinges, etc.

## *Production process*

1. Raw material warehouse

2. Lathe workshop

3. Assemble workshop

4. Quality inspection

5. Finished products

6. Packing

## *Testing equipment*

1. Agilent current testing




2. Quadratic element

3.Load Curve Meter

4.Bond Test

5.Life Fatigue Test

6.Microscope

## *Packing & delivery*

**Standard products will be delivered out within 3 days. Customized products will be sent out within 15 days.**