Product Specification

Model	SF-420*4850
Material	Copper Alloy
Current Rating	10A
Contact resistance (initial)	15mΩ
Full compression travel	≥9.0mm
Recommended work travel	450±20%（6.5mm）

Product Drawing



Our Service

1. We can reply yourinquiry within 24 working hours.

2. Customizeddesign is available and OEM are welcomed.

3. We can deliverthe probe pins to our clients all over the world with speed and precision.

4. We can providethe lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locati ng, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

production flow

1. Raw material warehouse

2. Lathe workshop

3. Assemble workshop

4. Quality inspection

5. Finished products

6. Packing

Packing Picture

shipping information



Factory Image

SFENG胜峰探针
（宁波）有限公司
仪表人员
金沅创新产业园