
Product Specification

Brand	SFENG		
Item number	SF-PH-1		
Plunger	Phosphor bronze		
Barrel	Phosphor bronze		
Spring	SUS or Music wire		
Spring Force	100g		
Full Travel	3.5		
Current Ration	ЗА		
Current Resistance	50mW		
Pitch	1.70		
Mounting hole size	1.0/1.05		
MOQ	100 pcs		
Lead time	7 working days after receiving the payment		

Product Picture

SF-PH10.12.18.23.32.45



规格 Spec 型号 Type	SF-PH-10	SF-PH-12	SF-PH-18	SF-PH-23	SF-PH-32	SF-PH-45
Α	1.20	1.50	2.00	2.50	3.50	5.00
В	0.75	0.95	1.29	1.80	2.50	3.50
С	1.20	1.50	2.00	2.50	3.50	5.00
D	0.98	1.34	1.83	2.33	3.23	4.55
E	0.98	1.27	1.77	2.27	3.17	4.55
F	0.47	0.56	0.75	1.25	1.62	2.45
a	7.0	10.0	16.0	16.0	16.0	16.0
b	9.5	13.0	16.0	18.0	18.0	19.5
С	20.5	27.0	36.0	38.0	38.0	40.0
d	1.0	2.0	2.0	3.0	3.0	4.0
e	1.0	2.0	2.0	3.0	3.0	1.5
行程 Full travel	3.5	6.0	8.3	10.5	10.0	10.5
钻孔尺寸 Mounting hole siza	1.0/1.05	1.3/1.35	1.8/1.85	2.3/2.35	3.2/3.25	4.65/4.7
最小间距 Recommended min.center	1.70	2.00	2.50	3.00	4.20	5.50
弹簧压力 Spring force	100g	150g	150g	150g	200g	250g
针轴材质 Bress,Ni.plated	磷铜	磷铜	磷铜	磷铜	磷铜	磷铜
接线形式	焊接	焊接	焊接	焊接或插 端子线	焊接或插 端子线	焊接或指 端子线

www.shengfengdz.com



Our Service

- 1. We can reply your inquiry within 24 working hours.
- 2. Customized design is available and OEM are welcomed.
- 3. We can deliver the probe pins to our clients all over the world with speed and precision.
- 4. We can provide the lowest price with high quality product to our client

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Batt ery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;


Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control



Packing Picture

