


Spring loaded plug-in type contact pogo pin

Specification

Item Name	Spring loaded plug-in type contact pogo pin
Material and finishes	Plunger:Brass,gold plated over nickel plated; Barrel:Brass,Gold plated over Nickel plated; Spring:Stainless steel;
Spring force	customized;
Lead time	3-10 days
Shipment	DHL/TNT/UPS/FEDEX











P/N	Total Length (L0)	Working Height (L1)	Spring Force $\pm 20\%$	Barrel Length (L2)	Length (L3)	Plunger Diameter (D0)	Barrel Diameter (D1)	Bottom Diameter (D2)	Tail length (D4)
N050M0	4.75	3.95	90.00	3.50	2.80	0.80	1.25	2.00	0.40
N059M0	8.10	5.80	100.00	5.80	3.00	0.80	1.60	2.80	2.30
N027M9	8.70	7.70	110.00	7.50	5.80	1.00	1.51	1.80	0.60
N029M3	10.90	9.50	110.00	11.20	8.20	1.00	1.51	1.80	2.50
N003M0	11.40	10.40	100.00	6.30	5.50	0.90	1.60	1.90	2.40
N029M2	13.70	12.50	110.00	11.00	10.50	1.00	1.51	1.80	2.50
N021X0	14.10	11.10	130.00	8.00	7.50	1.30	2.01	2.20	4.00
N021X5	14.10	11.10	200.00	8.00	7.50	1.30	2.01	2.20	4.00
N029M1	15.50	13.50	130.00	11.00	10.50	1.00	1.51	1.80	2.50
N029M0	17.20	16.20	100.00	15.70	13.20	1.00	1.51	1.80	2.50
N089M0	5.50	4.50	110.00	4.00	4.00	1.00	2.00	1.51	1.40
N130M1	7.10	6.40	50.00	6.10	4.30	0.80	1.20	1.30	0.80
N153M0	7.20	5.70	80.00	8.05	4.90	0.90	1.50	1.50	3.15
H255M1	7.40	5.90	40-60	5.80	5.40	0.90	1.51	2.00	2.00
N130M0	7.65	6.95	35.00	6.00	4.45	0.50	0.90	1.00	0.55
N059M1	8.10	5.80	100.00	5.80	3.00	0.80	1.60	2.80	1.30
N059M5	8.25	6.75	65.00	5.95	2.90	0.76	1.70	2.80	2.55
N059M2	8.50	6.20	100.00	6.20	3.20	0.80	1.60	2.80	1.50
N065M0	9.20	7.93	240.00	7.10	4.90	1.05	1.93	2.40	1.20
N059M3	9.30	8.30	100.00	7.00	3.70	0.80	1.60	2.80	2.80
N164M0	4.50	3.50	110.00	3.25	2.45	0.90	1.50	1.90	6.00
N181M2	4.80	4.00	110.00	4.10	2.40	1.03	1.50	2.10	0.80
N160M0	5.50	4.10	140.00	4.00	4.00	0.90	1.50	1.50	2.00
N181M6	6.40	5.50	100.00	5.00	4.50	1.00	1.51	2.00	0.80
N181M8	6.70	5.80	100.00	6.10	4.80	1.00	1.50	2.00	0.80
N181M0	7.20	6.20	110.00	6.00	4.60	1.00	1.48	1.80	0.60
N181M4	8.70	7.70	110.00	7.50	6.20	1.00	1.48	2.00	0.80
N157M0	10.30	8.50	60.00	8.30	6.30	1.70	2.60	2.60	2.00
N153M2	10.70	9.70	80.00	9.20	3.70	0.90	1.52	1.52	5.50

SFENG Probe factory introduction

Suzhou Shengyifurui Electronic Technology Co.,Ltd is specializing in the spring probe&the pogo pin with high quality,low price and fast delivery.We have our own brand,we always devote ourselves to achieving international standards,our company have passed the ISO9001-2008 quality managements certification and our products are qualified of RoHs.

Quality Test equipment

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

Packaging

