Product Picture

SF-GP SeriesItem

Item	Specification & Size				Drilling hole size
GP2.4	Barrel (A)	ϕ2.4mm	Plunger (D)	ϕ1.75mm	ϕ2.40mm
GP3.2	Barrel (A)	ϕ3.2mm	Plunger (D)	ϕ2.50mm	ϕ3.20mm
GP4.0	Barrel (A)	ϕ4.0mm	Plunger (D)	ϕ3.50mm	ϕ4.00mm
GP5.0	Barrel (A)	ϕ5.0mm	Plunger (D)	ϕ4.00mm, ϕ6.00mm	ϕ5.00mm
GP5.2	Barrel (A)	ϕ5.2mm	Plunger (D)	ϕ4.00mm, ϕ6.00mm	ϕ5.20mm
GP6.0	Barrel (A)	ϕ6.0mm	Plunger (D)	ϕ5.00mm	ϕ6.00mm

Our Service

1. We can reply your inquiry within 24 working hours.

2. Customized design is available and OEM are welcomed.

3. We can deliver the probe pins to our clients all over the world with speed and precision.

4. We can provide the lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locati ng, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control

Packing Picture