

Surgical Pogo Pin SF-PA5.8 by 36-J/M3

Specification

| | |
|------------------------------|---|
| Item Name | Surgical Pogo Pin SF-PA5.8 by 36-J/M3 |
| Material and finishes | Plunger:Brass,gold plated over nickel plated; Barrel:Brass,Gold plated over Nickel plated; Spring:Stainless steel; |
| Spring force | 400g |
| Lead time | 3-10 days |
| Shipment | DHL/TNT/UPS/FEDEX |

EW/r-9EX8-SVd-JS

Materials (Plated) (材質與鍍層):
 Barrel (針套) : Brass (黃銅) , Au on Ni Plated
 Plunger (針軸) : Brass (黃銅) , Au on Ni Plated
 Spring (彈弓) : SUS304 (不鏽鋼) , /

Specifications (技術要求):
 Contact Resistance (接觸電阻) : 50mΩ
 Full Stroke (滿行程) : 10mm
 Spring Force (額定彈力) : 400±10%gf@ load 10mm







| | | | | | | |
|----|----|-------|-----|------------------|-------------|--|
| | | | | 名稱 | 胜峰探针 | |
| | | | | SF-PA5.8X36-J/M3 | | 说明: 1、所有尺寸的单位为mm 2、未注图示尺寸公差: 按GB1804-79 11级精度执行。 |
| 标记 | 页数 | 更改文件号 | 签字 | 日期 | | |
| 设计 | | | 标准化 | | 图样标记 | |
| 校对 | | | 审定 | | 质量比例 | |
| 审核 | | | 制图 | 徐松孟 | S A 4:1 | |
| 工艺 | | | 日期 | 2016.10.07 | 共 1 页 第 1 页 | |



SFENG Probe factory introduction

Suzhou Shengyifurui Electronic Technology Co.,Ltd is specializing in the spring probe&the pogo pin with high quality,low price and fast delivery.We have our own brand,we always devote ourselves to achieving international standards,our company have passed the ISO9001-2008 quality managements certification and our products are qualified of RoHs.

Quality Test equipment

| | | |
|--|--|---|
| Spring exhausted tester | DC power supply | Current resistance tester |
|  |  |  |
| Microscope | Tensile strength tester | Spring tester |
|  |  |  |

Packaging

