# Double Head contact Pogo Pin Connector

Specification:

| | |
|---|---|
| Brand | SFENG PROBE |
| Item Number | **Double head pogo pin** GB031D570D20-BB-A6 |
| Material | Plunger : Becu / Gold Plated<br>Plunger : Becu / Gold Plated<br>Barrel : PhBz / Gold Plated<br>Spring : Music wire / Gold Plated |
| Spring force | 20g |
| Recommended travel | 0.65mm |
| Full travel | 1.1mm |
| Pitch | 0.45 |
| Contact Resistance | 100m ohm |
| Cycle time | 100,000times |
| MOQ | 100PCS if we have stock |
| Lead time | 2-15days after receiving the payment |




Our Advantages:

1.we have 30 years experience in probe pin and have ourself factory.

2.we provide free sample and have a testing depa rtment.

3.we could manufacture products as your request.

4.we guarantee best price and good service.

Our Main Product:

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semic onductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ a nd VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig loc ks, POM, Iron hinge etc

Testing Equipment:

| Spring exhausted tester | DC power supply | Current resistance tester |
| --- | --- | --- |
| | | |
| Microscope | Tensile strength tester | Spring tester |
| | | |

Package: