## Product Specification

| | |
|---|---|
| Brand | SFENG |
| Item number | SF-P030-A |
| Plunger | Brass or Becu,gold or Ni plated |
| Barrel | Brass,gold or Ni plated |
| Spring | SK4,music wire |
| Spring Force | 60g |
| Full Travel | 2.0mm |
| Current Ration | 1A |
| Current Resistance | 150mΩ |
| Pitch | 0.9mm |
| Mounting hole size | 0.65mm |
| MOQ | 100 pcs |
| Lead time | 7 working days after receiving the payment |

## Product Picture

## Probe specifications SF-P030 PL030(技术规格)

- Recommended minimum center(最小间距):
  0.90m(.0354 " )
- Mounting hole size(钻孔尺寸): 0.65mm(.0256 " )
- Full travel(行程): 2.0(.0787 " )
- Spring force(弹簧压力): 60g(克)
- Materials and finishes(材料及涂饰):
  Plunger:SK4,Rh plated
  Barrel:Phosphor bronze,Gold plated
  Spring:Music wire,Gold plated
- Current ration(额定电流): 1A(安培)
- Contact resistance(接触电阻): 150mΩ(毫欧姆)

Receptacle specifications
Materials and finishes: Phosphor bronze,
Gold plated




SF-P030-B

## *Our Service*

1.Reply your inquiry withn 24 working hours

2.Customized design is available,OEM are welcomed

3.Delivery the probe pins to our clients all over the world with speed and precision

4.provide the lowest price with high quality to our client

## *Main Products*

---Spring loaded pin(single) for PCB,ICT,FCT testing,etc;

---Pogo pin(connector) to establish a(usuallytemporary)connection between

two printed circuit boards for charing, locating, Battery, Semiconductor &

interconnectApplications;

---Double ended probef orBGA&semiconudtion testing;

---Universal pin without spring,coatingpin,LM pin withQZ&VZseries;

---High current probe,Switch probe,Capacitance needle...

---Terminal&receptacle/socket;

---Other related electronic compents,30#OKwire,Jig locks,POM,Ironhinge,etc

## *Quality Control*

| Spring exhausted tester | DC power supply | Current resistance tester |
|---|---|---|
| | | |
| Microscope | Tensile strength tester | Spring tester |
| | | |

## *Packing Picture*


胜峰电子