

Product Specification

| | |
|--------------------|--|
| Brand | SFENG |
| Item number | SF-PH15 |
| Plunger | Phosphor bronze/brass |
| Barrel | Phosphor bronze/brass |
| Spring | SUS or Music wire |
| Spring Force | 300g |
| Full Travel | 3.5 |
| Current Ration | 5A |
| Current Resistance | 50mW |
| Pitch | 3.50(0.1378") |
| Mounting hole size | 3.00(0.1181") |
| MOQ | 100 pcs |
| Lead time | 7 working days after receiving the payment |

Product Picture



Our Service

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.
3. We can deliver the probe pins to our clients all over the world with speed and precision.
4. We can provide the lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control

| | | |
|--|--|---|
| Spring exhausted tester | DC power supply | Current resistance tester |
|  |  |  |
| Microscope | Tensile strength tester | Spring tester |
|  |  |  |

Packing Picture

