Product Specification

Brand	SFENG
Item number	SF-P75
Plunger	brass
Barrel	brass
Spring	SUS or Music wire
Spring Force	120g
Full Travel	3.35(0.1319'')/2.5(0.0984'')
Current Ration	ЗА
Current Resistance	50mW
Pitch	1.90(0.0748'')
Mounting hole size	1.35(0.0532")/1.40(0.0551")
MOQ	100 pcs
Lead time	7 working days after receiving the payment

Product Picture





Our Service

- 1. We can reply your inquiry within 24 working hours.
- 2. Customized design is available and OEM are welcomed.
- 3. We can deliver the probe pins to our clients all over the world with speed and precision.
- 4. We can provide the lowest price with high quality product to our client

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;

Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Batt ery, Semiconductor & Interconnect applications;

Double ended probe for BGA and Semiconductor testing;

Universal pin without spring, coating pin, LM pin with QZ and VZ series;

High current probe, Switch probe, Capacitance needle;

Terminal & receptacle /socket;

Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control



Packing Picture

