

Product Specification

| | |
|--------------------|--|
| Brand | SFENG |
| Item number | SF-P156 |
| Plunger | Brass or Becu,gold or Ni plated |
| Barrel | Brass,gold or Ni plated |
| Spring | SK4,music wire |
| Spring Force | 250g |
| Full Travel | 6.3mm |
| Current Ration | 5A |
| Current Resistance | 50mΩ |
| Pitch | 4.75mm |
| Mounting hole size | 2.75mm |
| MOQ | 100 pcs |
| Lead time | 7 working days after receiving the payment |

Product Picture





chinapogopinsupplier.com

Our Service

- 1.Reply your inquiry withn 24 working hours
- 2.Customized design is available,OEM are welcomed
- 3.Delivery the probe pins to our clients all over the world with speed and precision
- 4.provide the lowest price with high quality to our client

Main Products

- Spring loaded pin(single) for PCB,ICT,FCT testing,etc;
- Pogo pin(connector) to establish a(usuallytemporary)connection between two printed circuit boards for charging, locating, Battery, Semiconductor &

interconnectApplications;

---Double ended probef orBGA&semiconudtion testing;







---Universal pin without spring,coatingpin,LM pin withQZ&VZseries;

---High current probe,Switch probe,Capacitance needle...

---Terminal&receptacle/socket;

---Other related electronic compents,30#OKwire,Jig locks,POM,Ironhinge,etc

Quality Control

| Spring exhausted tester | DC power supply | Current resistance tester |
|---|---|--|
|  |  |  |
| Microscope | Tensile strength tester | Spring tester |
|  |  |  |

Packing Picture

