

**Conectores de mola do contato do pino de pogo da corrente 3A SF-PPA5.8 \* 36-J / M3**

# Especificação

|                               |  |
|-------------------------------|--|
| <b>Item Nome</b>              | <b>Conectores de mola do contato do pino de pogo da corrente 3A SF-PPA5.8 * 36-J / M3</b>  |
| <b>Material e acabamentos</b> | <b>Êmbolo: Latão banhado a ouro sobre níquel;<br/>Barril: Latão, banhado a ouro sobre níquel;<br/>Primavera: aço inoxidável;</b> |
| <b>Força da primavera</b>     | <b>400g</b>  |
| <b>Conduzir Tempo</b>         | <b>3-10 dias</b>   |
| <b>envio</b>                  | <b>DHL / TNT / UPS / FEDEX</b>   |

EW/f-9EX8-SWd-JS

**Materials(Plated) (材質與鍍層):**  
 Barrel(針套) : Brass(黃銅) , Au on Ni Plated  
 Plunger(針軸) : Brass(黃銅) , Au on Ni Plated  
 Spring(彈弓) : SUS304(不鏽鋼) , /

**Specifications (技術要求):**  
 Contact Resistance(接觸電阻) : 50mΩ  
 Full Stroke(滿沖程) : 10mm  
 Spring Force(額定彈力) : 400±10%gf@ load 10mm







|    |    |       |     |                  |       |  |  |
|----|----|-------|-----|------------------|-------|--|--|
|    |    |       |     | 名稱               |       | 勝峰探針   |  |
|    |    |       |     | SF-PA5.8X36-J/M3 |       | 說明: 1、所有尺寸的单位为mm<br>2、未注图示尺寸公差:<br>按GB1804-79 11级精度执行。 |  |
| 标记 | 数量 | 更改文件号 | 签字  | 日期               | 图样标记  | 质量比例   |  |
| 设计 |    |       | 标准化 |                  | S A   | 4:1  |  |
| 校对 |    |       | 审定  |                  |       |  |  |
| 审核 |    |       | 制图  | 徐松孟              |       |  |  |
| 工艺 |    |       | 日期  | 2016.10.07       | 共 1 页 | 第 1 页  |  |



## **SFENG Fábrica de sondas introdução**

Suzhou Shengyifurui Tecnologia Eletrônica Co Ltd é especializada na primavera sonda e o pino de pogo com alta qualidade, preço baixo e entrega rápida. Nós temos nossa própria marca, nós sempre nos dedicamos a alcançar os padrões internacionais, nossa empresa passou a ISO9001- Certificação de gestão de qualidade de 2008 e nossos produtos são qualificados de RoHs.

## Equipamento de teste de qualidade

|   |  |   |
|---|--|---|
| Spring exhausted tester   | DC power supply  | Current resistance tester   |
|  A tall, white, cabinet-style machine with a glass door on the upper half and a control panel on the right side. |  A white, rectangular device with a black front panel. It features a red power switch, several knobs, and output terminals. The text "YoRI ADJUSTABLE DC POWER SUPPLY" is visible on the panel. |  A white, rectangular device with a digital display showing "8.8.8.8" in green. It has a warning symbol and a control knob on the right side. |
| Microscope  | Tensile strength tester  | Spring tester   |
|  A white and black compound microscope with a stage, objective lenses, and an eyepiece.                         |  A blue and white machine with a vertical column and a horizontal arm, used for testing the tensile strength of materials.   |  A white machine with a digital display and a control panel, used for testing the properties of springs.                                     |

## Embalagem

