

Especificação do produto

marca	SFENG
número Item	SF-P11
Revestimento	Banhado a ouro
Tempo de espera	7 dias úteis após o recebimento do pagamento

SF-P11

Technical drawing of SF-P11 probe tip and main body. The tip shows various contact types: -A2, -E, -H1.3, -A, -U3, -H, -B, -U, -LM1.3, -J, -V1.3, -LM, -D1.0, -G2, -T1.3, -E1.0, -G1.3, -T, -E1.3, -G. The main body is labeled SP-P11-E with dimensions: 1.5, 4.0, 24, and diameters 1.5, 0.75, 1.01.

Probe specifications SF-P11(技术规格)

- Recommended minimum center(最小间距): 1.90mm(.0748 ")
- Mounting hole size(钻孔尺寸): 压克力: 1.35mm(.0532 ")
电木板、玻璃纤维板: 1.40mm(.0551 ")
- Full travel(行程): 4.0(.1575 ")
- Spring force(弹簧压力): 150g
- Materials and finishes(材料及涂饰):
Plunger: Be Cu, Rh plated
Barrel: Brass, Gold plated
Spring: Stainless steel
- Current rating(额定电流): 3A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

-15-

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

SF-R11

Technical drawing of SF-R11 probe tips. It shows various contact types: SF-R11-SC, SF-R11-SC4.0, SF-R11-CR, SF-R11-CR4.0, SF-R11-VCR, SF-R11-VSC, SF-R11-WW4.0, SF-R11-WW, SF-R11-VW. Dimensions include 2.5, 18.5, 23.5, 5.0, 31, 7.5, 0.64, 1.55, 1.44, 1.31, 1.2, 0.64, 1.55, 1.44, 1.31, 1.2, 0.64, 1.55, 1.44, 1.31, 1.2, 0.64.

Probe specifications SF-R11(技术规格)

- Recommended minimum center(最小间距): 1.90mm(.0748 ")
- Mounting hole size(钻孔尺寸): 压克力: 1.35mm(.0532 ")
电木板、玻璃纤维板: 1.40mm(.0551 ")
- Materials and finishes(材料及涂饰): Barrel: Brass, Gold plated
- Connections(接线形式):
Crimp: R11-VCR, R11-CR, R11-CR4.0
Solder cup: R11-VSC, R11-SC, R11-SC4.0
Wire wrap: R11-VW, R11-WW, R11-WW4.0

-16-

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)

Imagem do produto

SF-P11-J

SFENG
The China's The World's



WWW.SF-PROBE.COM

SF-P11-B

SFENG
The China's The World's



www.chinapogopinsupplier.com

Nosso serviço

1. Podemos responder à sua Dentro de 24 horas.
2. personalizado O projeto está disponível eo OEM é bem-vindo.
3. Podemos entregar A sonda pinos para nossos clientes em todo o mundo com velocidade e precisão.
4. Podemos fornecer O preço mais baixo com produtos de alta qualidade para nossos clientes.

Produtos Principais

Pino da mola (único) para PCBs, ICT, teste etc. de FCT;

Pogo pino (conector) para estabelecer a conexão entre as duas placas de circuito para o carregamento, localização, bateria, semicondutores & amp; amp; Aplicações de interconexão;

Sonda de ponta dupla para testes BGA e semicondutores;

Pino universal sem pino de revestimento de mola, pino LM com série QZ e VZ;

Alta sonda de corrente, interruptor sonda agulha capacitância;

Terminal & amp; amp; Receptáculo / ficha;

Outros componentes eletrônicos relacionados, fio # 30 OK, bloqueios Jig, POM, ferro charneira, etc

Controle de qualidade

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

Embalagem Foto

