

## Испытательный зонд 50 mils для PCB / ICT

### Материал и отделка

Плунжер: бронза или латунь или BeCu, позолоченные или никелированные;

Бочка: латунь, позолота или никелированная;

Пружина: нержавеющая сталь или музыкальный провод;

### Фотографий

- Любые советы, которые мы могли бы предоставить вам
- Если вас это интересует, свяжитесь со мной



### SF-P020

**Probe specifications SF-P020 (技术规格)**

- Recommended minimum center (最小间距): 1.0mm (.0394")
- Mounting hole size (钻孔尺寸): 0.75mm (.0295")
- Full travel (行程): 2.0(.0787")
- Spring force (弹簧压力): 80g(克)
- Materials and finishes (材料及涂饰): Plunger:SK4,Rh plated; Barrel:Phosphor bronze,Gold plated; Spring:Music wire,Gold plated
- Current raiton(额定电流): 1A(安培)
- Contact resistance(接触电阻): 120mΩ(毫欧姆)

**Receptacle specifications**  
Materials and finishes: Phosphor bronze, Gold plated

### SF-P50

**Probe specifications SF-P50 (技术规格)**

- Recommended minimum center (最小间距): 1.27mm (.0500")
- Mounting hole size (钻孔尺寸): V: 0.90mm (.0354") W: 0.95mm (.0374")
- Full travel (行程): 2.5(.0984")
- Spring force (弹簧压力): 100g
- Materials and finishes (材料及涂饰): Plunger:Be,Cu,Rh plated; SK4,Rh plated; Barrel:Phosphor bronze,Gold plated; Spring:Stainless steel
- Current raiton(额定电流): 1.5A(安培)
- Contact resistance(接触电阻): 50mΩ(毫欧姆)

Noted: Specifications subject to change without notice(注: 规格变动不另行通知)







## Наши преимущества

1. we имеет 30 лет опыта в пробке штыря и имеет ourself фабрику.
2. we обеспечивает свободный образец и имеет отдел испытания.
3. we смогло произвести продукты как ваш запрос.
4. we гарантируют самое лучшее цену и хорошее обслуживание.

## Наш основной продукт

Spring loaded pin (single) for PCB, ICT, FCT testing etc;  
Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;  
Double ended probe for BGA and Semiconductor testing;  
Universal pin without spring, coating pin, LM pin with QZ and VZ series;  
High current probe, Switch probe, Capacitance needle;  
Terminal & receptacle /socket;  
Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

**Контроль контрольного оборудования**

Spring exhausted tester	DC power supply	Current resistance tester
		
Microscope	Tensile strength tester	Spring tester
		

пакет

