

100mil ICT test probe SF-PA1.65 BY 32.3-LM2.0

Specifications

| | |
|--------------------|----------------------------------|
| Brand | SFENG |
| Model | SF-PA1.65X32.3-LM2.0 |
| Plunger | BeCu |
| Body | Brass |
| Spring | SWP |
| Spring force | 350g±50g |
| Working travel | 4.0mm |
| Plated | Gold plated |
| Contact Resistance | 50mΩ |
| Current Ration | 5A |
| Full Stroke | 5.30mm |
| MOQ | 1000 |
| Lead Time | 7-15 Days after confirming order |

Customized probe pin Image



Customized probe pin drawing



our service

1. Quick response.
2. Customized is accepted.
3. Short production time and fast delivery.
4. High quality and good price.

Main products

Spring-loaded pin (single) of PCB, ICT, FCT testing;

Spring pin (connector) to establish a connection between two printed circuit boards for charging, positioning, batteries, semiconductors and amplifiers; interconnect applications;

BGA and semiconductor test double-ended probe;

Universal pin no spring, paint needle, LM pin QZ and VZ series;

High current probe, the probe switches, capacitors needle;

Pier and amplifier; socket / socket;

Other related electronic components, 30 # OK line, jig lock, POM, iron hinges, etc.

Production process



Testing equipment



Packing & delivery

