

Production specifications

Item number	SF3883
Size	dia8.5*88.0mm
Material	Plunger:Te, Ni plated Barrel:Brass, Ni plated Spring:SWP, Ni plated
Rated Stroke	12.0mm
Spring force	1400±250gf@load 12.0mm 2000±400gf@load 18.0mm
MOQ	100PCS
Payment	T/T
Delivery time	5-15days after receiving the payment

Product Pictures



Production Flow



Testing Equipment



Packing



Main products

- 1.Spring loaded pin(single)for PCB,ICT,FCTtesting etc;
- 2.Pogo pin(connector)to establish connection between two printed circuit boards for charging,locating,battery,semiconductor&interconnector applications;
- 3.Double ended probes for BGA and semiconductor testing;
- 4.Universal pin without spring,coating pin,LM pin with QZ and VZ series;
- 5.High current probe,switch probe,capacitance needle;

6. Terminal & receptacle/socket;

7. Other related electronic components, Jig locks, POM and etc.

Whatever you want, please contact us without hesitation, and we will try our best to meet your requirement within our capability.

Our service

1. We can reply your inquiry within 24 working hours;

2. Customized design is available and OEM are welcomed;

3. We can deliver the probe pins to our clients all over the world with speed and precision.

4. We can provide the lowest price with high quality products to our clients.