

Product Picture

高频针SF-810 系列

SF810-B051-SG13		SF810-02	
SF810-A150-BG13		SF810-02S	
SF810-J051-BG13		SF810-06	
		SF-810-06S	

内芯探针
 针杆 铍铜或SK4镀金
 针管 磷铜管镀金
 工作弹力 1.3N(130g)
 2N(200g)
 最大电流 8-10安培
 接触电阻 50毫欧姆
 频宽 2.4GHZ
 接头 MCX

外芯针头
 材料 铍铜镀金

高频主体针
 外管 黄铜镀金
 内管 黄铜镀金
 内芯 铁氟龙
 工作弹力 4N(400g)
 8N(800g)

HRF810-40
 HRF810-80

R810
 针套 黄铜镀金

接头 "MCX" 型

Our Service

1. We can reply your inquiry within 24 working hours.
2. Customized design is available and OEM are welcomed.
3. We can deliver the probe pins to our clients all over the world with speed and precision.
4. We can provide the lowest price with high quality product to our client .

Main Products

Spring loaded pin (single) for PCB, ICT, FCT testing etc;
 Pogo pin (connector) to establish connection between two printed circuit boards for charging, locating, Battery, Semiconductor & Interconnect applications;
 Double ended probe for BGA and Semiconductor testing;
 Universal pin without spring, coating pin, LM pin with QZ and VZ series;
 High current probe, Switch probe, Capacitance needle;
 Terminal & receptacle /socket;
 Other related electronic components, 30# OK wire, Jig locks, POM, Iron hinge etc

Quality Control

Spring exhausted tester



DC power supply



Current resistance tester



Microscope



Tensile strength tester



Spring tester

