Production specifications

Item number	SF-P125-G1.35
Pitch	1.90mm
Mounting hole size	Pressure plate:1.35 Glass fiber board:1.40mm
Rated stroke	3.5mm
Full stroke	5.0mm
Spring force	150±20%gf@load3.5mm
Current ration	3A
Current resistance	≤50mΩ
MOQ	100PCS
Payment	T/T
Delivery time	5-10days after receiving the payment

Product Pictures

×

×

Production Flow

×

Testing Equippment

×

Packing

×

Main products

- 1.Spring loaded pin(single)for PCB,ICT,FCTtesting etc;
- 2.Pogo pin(connector)to establish connection between two printed circuit boards for charging,loc ating,battery,semiconductor&interconnector applications;
- 3. Double ended probes for BGA and semiconductor testing;
- 4. Universal pin without spring, coating pin, LM pin with QZ and VZ series;
- 5. High current probe, switch probe, capacitance needdle;
- 6.Terminal&receptacle/socket;

7.Other related electronic components, Jig locks, POM and etc.

Whatever you want, please contact us without hesitation , and we will try our best to meet your requirement within our capability.

Our service

- 1.We can reply your inquiry within 24 working hours;
- 2. Customized design is available and OEM are welcomed;
- 3.We can deliver the probe pins to our clients all over the world with speed and precision.
- 4.We can provide the lowest price with high quality products to our clients.