

Production specifications

Item number	SF6536
Size	dia3.0*42.5mm
Material	Plunger:Becu,Au on Ni plated Barrel:Brass, Au on Ni plated Insulation sleeve:PEEK Solder connection:Becu, Au or Ni plated
Switch path	1.7mm
Full stroke	5.2mm
Spring force	Head:100~150g Tail:200~250g
MOQ	100PCS
Payment	T/T
Delivery time	5-15days after receiving the payment

Product Pictures



Production Flow



Testing Equipment



Packing



Main products

- 1.Spring loaded pin(single)for PCB,ICT,FCTtesting etc;
- 2.Pogo pin(connector)to establish connection between two printed circuit boards for charging,locating,battery,semiconductor&interconnector applications;
- 3.Double ended probes for BGA and semiconductor testing;
- 4.Universal pin without spring,coating pin,LM pin with QZ and VZ series;

- 5.High current probe,switch probe,capacitance needdle;
- 6.Terminal&receptacle/socket;
- 7.Other related electronic components,Jig locks,POM and etc.

Whatever you want,please contact us without hesitation ,and we will try our best to meet your requirement within our capability.

Our service

- 1.We can reply your inquiry within 24 working hours;
- 2.Customized design is availble and OEM are welcomed;
- 3.We can deliver the probe pins to our clients all over the world with speed and precision.
- 4.We can provide the lowest price with high quality products to our clients.